

Figure 58 Aileron Control Installation

Index No.	Part No.	Description	Cond.
1	75-3346	Idler assy-aileron control, 2 required	N-S
	KS-4	Replacement bearing, 75-3346 idler, 2 required	F/N
	K-4	Replacement bearing, 75-3346 idler (hub end,) 2 req.	F/N
	Attach hdw.	1 ea. AN4-26, 1 ea. AN320-4, 1 ea. AN380-2-2, 2 ea. AN960-416	F/N
2	75-3313	Bellcrank assy-aileron control, 2 required	N-S
	KS-4	Replacement bearing, 75-3313 tube ends, 2 required	F/N
	K-4	Replacement bearing, 75-3313 hub end, 2 required	F/N
	Attach hdw.	1 ea. AN4-23, 1 ea. AN320-4, 1 ea. AN960-416, 1 ea. AN380-2-2	F/N
3	AG75-3325	Tube assy-aileron adjustable push pull w/eye & nut, 2 required	FAA-PMA
4	AG75-3325-2	Same as above except without eye & nut	FAA-PMA
	AGS-276-8S	Replacement bushing, flanged, 2 required	FAA-PMA
5	AG75-3355	Eye assy-aileron adjustable push pull tube, 2 req.	FAA-PMA
	AN316-6	Nut-check, AG75-3355 eye	F/N
	KS-4	Replacement bearing, AG75-3355 eye	F/N
	Attach hdw.	1 ea. AN24-18, 1 ea. AN320-4, 1 ea. AN24-19, 2 ea. AN380-2-2	F/N

AILERON CONTROL INSTALLATION - R-670, PT-17, N2S-4 & R-680, PT-13, N2S-5 continued

Figure 58

Index

No.	Part No.	Description	Cond.
6	75-3327	Tube assy-aileron push pull lh	N-S
7	75-3327-1	Tube assy-aileron push pull rh	N-S
	AGS-276-8S	Replacement bushing, 75-3327, 3327-1 tubes, 4 req.	FAA-PMA
	Attach hdw.	2 ea. AN24-19, 2 ea. AN320-4, 2 ea. AN380-2-2	F/N
8	75-3349	Link assy-aileron control, 2 required	N-S
	S-226-10S	Replacement bushing-3/8" press, 75-3349 link, 4 req.	N-P
	KS-4	Replacement bearing, 75-3349 link, 2 required	F/N
	Attach hdw.	1 ea. AN24-18, 1 ea. AN24-19, 2 ea. AN320-4, 3 ea. AN960-416, 2 ea. AN380-2-2	F/N
	75-3326-1	Bolt-aileron horn control stop, 2 required	N-S
	AN316-4	Nut, 75-3326 bolt, 2 required	F/N
	AN364-428A	Nut, 75-3326 bolt, 2 required	F/N

HYDRAULIC BRAKE INSTALLATION - R-670, PT-17, N2S-4, R-680, PT-13, N2S-5




Figure 59 Hydraulic Brake Installation